


## TWO-WAY RADIC



National Coverage\*
Instant Clear Audio
High Capacity Li-ion Battery
Compact & Durable
50 Group Channels
Dispatcher with GPS Location
USB Charger
Platforms: HY or REALPTT

## PTT Two - Way Radio IP GSM NETWORK HEAVY DUTY



Cartek ZA-P7

















Profession FM Padio

## Specification

Farance Barre	
Frequency Range	GSM: Band 2/3/8, CDMA 1XBCO CDMA2000; Evdo Rev.A 800MHz TD-SCDMA: Band 34/39, WCDMA: Band 1/5/8 TDD-LTE: Band 38/39/40/41, FDD-LTE: Band 1/3/5
Max Groups	50
Working Voltage	3.3V - 4.20V : 3.8V
Operating Temperature Range	-30℃~ +80℃
Dimension excl Antenna (L×W×H)	130mm×60mm×40mm
Weight (including Antenna and Battery)	250g
Battery Capacity	4400mAH
Battery Operating Time Average	25 hours on 5:5:90 duty cycle
Charge Time: USB	6 hours
Data Usage Standby	100 bytes per 20 seconds
Date Usage Transmit / Receive	500 bytes per second
Average Data Use Per Day	3 - 4 MB
Max RF Power	23dBm – 25dBm
Receiving Signal Sensitivity	-106dBm

IP54

- \* This radio connects to an Internet Network (IP) via the preloaded data SIM card (GSM) inserted at the back.
- \* Coverage is country wide and depends on network availability.
- ZA-P7 links to a Server Platform to direct calls.
- Compatible Platforms: HY or REALPTT
- \* There may be an annual or monthly cost, arranged by the dealer, to access the platform.
- Each radio needs activation of Serial Number before use.
- \* The dealer can setup selective groups for intercommunication.
  \* <u>Dispatcher PC software</u> is available, via the dealer, to contact single or groups of radios, to check GPS map position of radios..







Rating Water / Dust proof