

## DS-UPS600 (SA) UPS



### Key Feature

- Compact size
- Excellent microprocessor control guarantees high reliability
- 4-6 hours recover to 90% capacity





## ▪ Specification

Parameters	
Protection Method	Overload, discharge, and overcharge protection
Operating Temperature and Humidity	0 °C to 40 °C (32 °F to 104 °F). Humidity 30% to 90% (non-condensing)
Weight	Approx. 4.2 kg (9.26 lb)
Dimension	274 mm × 95 mm × 139 mm (10.79" × 3.74" × 5.47")
LED Indicator	Working Mode (AC Mode): Solid green (Flashing green when the battery is charging) Charging Mode (DC Mode): Solid red Overloading Mode: Flashing yellow
Alarm	Charging Mode (DC mode): Sounding three times Low Battery: Sounding three times Overloading Mode: Sounding every 0.5 seconds Fault: Continuously sounding
Storage Conditions	-10 °C to 50 °C (14 °F to 122 °F). Humidity 20% to 95% (non-condensing)
Capacity	600 VA / 360 W
Input Voltage Range	220 VAC to 240 VAC
Input Frequency Range	50/60 Hz
AC Voltage Regulation (Batt. Mode)	220 VAC to 240 VAC
Frequency Range (Batt. Mode)	50/60 Hz ± 0.5 Hz
Transfer Time	DC to AC ≤ 10 ms; AC to DC ≤ 10 ms
Waveform (Batt. Mode)	Charging Mode (DC Mode): PWM
POWER	
Battery	12 V/7 Ah × 1
Rechargeable	4-6 hours recover to 90% capacity

## ▪ Available Model

DS-UPS600 (SA)

## ▪ Dimension



**Headquarters**

No.555 Qianmo Road, Binjiang District,  
Hangzhou 310051, China  
T +86-571-8807-5998  
www.hikvision.com



Follow us on social media to get the latest product and solution information.

